FUJIFILM

DIGITAL CAMERA -T200

New Features Guide

Version 1.10

Features added or changed as a result of firmware updates may no longer match the descriptions in the documentation supplied with this product. Visit our website for information on the updates available for different products:

https://fujifilm-x.com/support/download/firmware/

Contents

X-T200 firmware version 1.10 adds or updates the features listed below. For information on earlier versions, visit the following website.

http://fujifilm-dsc.com/en/manual/

No.	Description	X-T200	See	Ver.
1	The Z CONNECTION SETTING > USB IMAGE TRANSFER SETTING item in the setup menu has been renamed USB MODE and now contains an option that lets the camera serve as a webcam.		1	1.10



Changes and additions are as follows.

X-T200 Owner's Manual: 📖 176 Ver. 1.10 **USB MODE**

Choose a mode for USB connections to computers, smartphones, and tablets

Option	Description			
USB CARD READER	Pictures can be transferred when the camera is connected			
000 0000	to a computer, smartphone, or tablet via USB.			
USB WEBCAM	When connected to a computer via USB, the camera func-			
OJD WEDCAM	tions as a webcam.			
OFF	Data transfer is disabled when the camera is connected to a			
Urr	computer, smartphone, or tablet via USB.			



- Select **USB CARD READER** for **USB MODE** before connecting the USB cable to transfer pictures to a computer, smartphone, or tablet (X-T200 Owner's Manual, 205).
 - Select **USB WEBCAM** for **USB MODE** before connecting the camera for use as a webcam. "FUJIFILM X-T200" will be displayed when the computer detects the camera.
 - The webcam feature is supported under Windows 10 (x64), macOS 10.14 (Mojave), and macOS 10.15 (Catalina).
 - When USB WEBCAM is selected:
 - III IMAGE QUALITY SETTING and III SHOOTING SETTING cannot be adjusted.
 - apart from the **ON/OFF** button and rear command dial (which can be used only for exposure compensation), camera controls cannot be used,
 - M AF/MF SETTING > PRE-AF is fixed at ON and the camera focuses only on the subject in the center focus area,
 - MR AF/MF SETTING > FACE/EYE DETECTION SETTING is set to FACE DETECTION ON
 - HDMI output is not available,
 - audio from built-in and external microphones is not output to the connected device.
 - images are not displayed in the LCD monitor, and
 - the AF lamp will light if the battery is low; insert a spare battery if available.
 - For more information on web conferencing, see the documentation for the web conference application.

FUJIFILM

FUJIFILM Corporation

7-3, AKASAKA 9-CHOME, MINATO-KU, TOKYO 107-0052, JAPAN https://fujifilm-x.com













